




Flag2Go


INSTRUCTIONS



- A - Base Connector
- B - Treaded Base Connector
- C - Square Connector
- D - Mast holder
- E - Collar
- F - Long Screw
- G - Short Screw
- H - Ring (not needed)


Before Beginning: Please remove all the rings from the mast and top bar. In order to make assembly easier the graphic is sleeved so the rings are not needed.

A. Assemble the Base




1

Join the four plastic water tanks with the threaded base connectors (B) on the bottom and the base connectors (A) on the top.




2

Secure the base connectors (A & B) with the long screw (F).



3


Place the top and bottom square connectors (C) in the center of the base.



4

Insert the mast holder (D) from the bottom with the threads on top.

B. Insert the Pole




5

Secure the mast holder (D) with the collar (E).




6

Place base in desired location and fill with water.



7

Place the mast into the center hole and the four support poles in the corners.




8

Secure the support poles by pushing the locking plastic bracket into position.


Note: If the support legs don't reach the corners, loosen and lower the mast ring.

C. Attach the Graphic




9

Place the sleeve on the side of the graphic over the mast pole.



10

Insert the horizontal bar into the sleeve on the top of the banner.




11

Secure the horizontal bar by screwing the short screw (G) into the top of the mast.



12

Locate the velcro tab at the end of the sleeve. Remove the protective backing and apply the adhesive layer directly to the pole. (Note: When disassembling flag, simply unzip velcro pieces from each other.)



13

Lift the mast one section at a time, making sure that every section clicks into position.